Environmental Protection Agency

(k) The authorities listed under $\S 60.50c(i)$ shall be retained by the Administrator and not be transferred to a state

[60 FR 65414, Dec. 19, 1995, as amended at 74 FR 51402, Oct. 6, 2009; 76 FR 18412, Apr. 4, 2011]

§ 60.33e Emissions guidelines.

- (a) For approval, a State plan shall include the requirements for emissions limits at least as protective as the following requirements, as applicable:
- (1) For a designated facility as defined in §60.32e(a)(1) subject to the emissions guidelines as promulgated on September 15, 1997, the requirements listed in Table 1A of this subpart, except as provided in paragraph (b) of this section.
- (2) For a designated facility as defined in §60.32e(a)(1) subject to the emissions guidelines as amended on October 6, 2009, the requirements listed in Table 1B of this subpart, except as provided in paragraph (b) of this section.
- (3) For a designated facility as defined in §60.32e(a)(2), the more stringent of the requirements listed in Table 1B of this subpart and Table 1A of subpart Ec of this part.
- (b) For approval, a State plan shall include the requirements for emissions limits for any small HMIWI constructed on or before June 20, 1996. which is located more than 50 miles from the boundary of the nearest Metropolitan Statistical Standard Area (defined in §60.31e) and which burns less than 2,000 pounds per week of hospital waste and medical/infectious waste that are at least as protective as the requirements in paragraphs (b)(1) and (b)(2) of this section, as applicable. The 2,000 lb/week limitation does not apply during performance tests.
- (1) For a designated facility as defined in §60.32e(a)(1) subject to the emissions guidelines as promulgated on September 15, 1997, the requirements listed in Table 2A of this subpart.
- (2) For a designated facility as defined in §60.32e(a)(1) subject to the emissions guidelines as amended on October 6, 2009, the requirements listed in Table 2B of this subpart.
- (c) For approval, a State plan shall include the requirements for stack

opacity at least as protective as the following, as applicable:

- (1) For a designated facility as defined in §60.32e(a)(1) subject to the emissions guidelines as promulgated on September 15, 1997, the requirements in §60.52c(b)(1) of subpart Ec of this part.
- (2) For a designated facility as defined in \$60.32e(a)(1) subject to the emissions guidelines as amended on October 6, 2009 and a designated facility as defined in \$60.32e(a)(2), the requirements in \$60.52c(b)(2) of subpart Ec of this part.

[74 FR 51403, Oct. 6, 2009]

§ 60.34e Operator training and qualification guidelines.

For approval, a State plan shall include the requirements for operator training and qualification at least as protective as those requirements listed in §60.53c of subpart Ec of this part. The State plan shall require compliance with these requirements according to the schedule specified in §60.39e(e).

§ 60.35e Waste management guidelines.

For approval, a State plan shall include the requirements for a waste management plan at least as protective as those requirements listed in §60.55c of subpart Ec of this part.

§ 60.36e Inspection guidelines.

- (a) For approval, a State plan shall require each small HMIWI subject to the emissions limits under §60.33e(b) and each HMIWI subject to the emissions limits under §60.33e(a)(2) and (a)(3) to undergo an initial equipment inspection that is at least as protective as the following within 1 year following approval of the State plan:
- (1) At a minimum, an inspection shall include the following:
- (i) Inspect all burners, pilot assemblies, and pilot sensing devices for proper operation; clean pilot flame sensor, as necessary;
- (ii) Ensure proper adjustment of primary and secondary chamber combustion air, and adjust as necessary;
- (iii) Inspect hinges and door latches, and lubricate as necessary;
- (iv) Inspect dampers, fans, and blowers for proper operation;